

CorePro LED PLT 4P

CorePro LED PLT HF 6.5W 830 4P GX24q-2

The CorePro LED PLT 4P integrates a LED light source into a traditional fluorescent form factor. This product is the ideal solution for uplamping in general lighting applications: it meets basic lighting requirements, offers significant energy savings, and is environmentally friendly

Product data

General Information	
Lighting Technology	LED
Flux measurement reference	Sphere
Switching Cycle	200,000
Nominal lifetime	30,000 hour(s)
Cap-Base	GX24Q-2 [GX24q-2]

Light Technical	
Color Code	830 [CCT of 3000K]
Beam Angle (Nom)	120 degree(s)
Luminous Flux	720 lumen
Color Designation	White (WH)
Correlated Color Temperature (Nom)	3000 K
Luminous Efficacy (rated) (Nom)	110 lm/W
Color Consistency	<6
Color rendering index (CRI)	82
LLMF At End Of Nominal Lifetime (Nom)	70 %

Operating and Electrical	
Line Frequency	20K-80K Hz
Input Frequency	20K-80K Hz
Power Consumption	6.5 W
Starting Time (Nom)	0.5 s
Warm-up time to 60% light	0.5 s
Power Factor (Fraction)	0.9
Voltage (Nom)	20-60 V

Temperature	
Ambient temperature range	-20 °C to 35 °C
T-Case Maximum (Nom)	65 °C

Controls and Dimming	
Dimmable	No

Mechanical and Housing	
Bulb Finish	Frosted
Bulb Material	Plastic
Product Length	100 mm
Bulb Shape	Tube, single-ended

Approval and Application	
Energy Efficiency Class	F
Energy Saving Product	Yes
Approval Marks	RoHS compliance TUV CE marking KEMA Keur certificate
Energy Consumption kWh/1000 h	7 kWh

CorePro LED PLT 4P


EPREL Registration Number	1361420
CE mark	Yes
EU RoHS compliant	Yes

Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	20
Material number (12NC)	929003576302
Full product name	CorePro LED PLT HF 6.5W 830 4P GX24q-2
EAN/UPC - Case	8719514487772

Product Data


Full product code	871951448776500
Order product name	CorePro LED PLT HF 6.5W 830 4P GX24q-2
Order code	929003576302

Dimensional drawing




Product	D1	D2	A1	A2	A3
CorePro LED PLT HF 6.5W 830 4P GX24q-2	42 mm		93 mm	103 mm	119 mm


Photometric data



General uniform lighting - CorePro LED PLT HF 6.5W 830 4P GX24q-2




Light Distribution Diagram




Spectral Power Distribution Colour


Lifetime




Lumen Maintenance Diagram




Life Expectancy Diagram - CorePro LED PLT HF 6.5W 830 4P GX24q-2



Life Expectancy Diagram



Life Expectancy Diagram



Lumen Maintenance Diagram - CorePro LED PLT HF 6.5W 830 4P GX24q-2

CorePro LED PLT 4P

© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.