GRIDPRO

Technical Specification

Product Code: GM2300BK **Description:** USB Throughput Data Module



General Information

Dimensions (mm)	24.5 (W) x 50 (H) x 40 (D)		
Finish	Black		
Materials	Front Cover: Nylon Fixing Screws: Nickel Plated Steel	Electronics: USB Connections & Cable	
Anti Microbial Certified	No		
Rated Voltage (DC)	30		
Resistive Load Rating (A)	2		
USB Output Type	USB Type "A"		
Flylead Cable Length (mm)	30		
Flylead Overall Length (mm)	95		
Minimum Back Box Depth (mm)	47		
Ingress Protection	IP20		
Operational Temperature (°C)	-5 to +40		
Warranty (Years)	10	Warranty - Electronics (Years)	1

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

UK Patent: GB 2578427

CLIP-ON MODULES SCREW-IN MODULES

Scolmore House, Mariner, Lichfield Road Industrial Estate,
Tamworth, Staffordshire, B79 7UL United Kingdom
T: +44 (0)1827 63454 | **F:** +44 (0)1827 63362
E: sales@scolmore.com | **W:** scolmore.com

DoC Installation