EMPTY ENCLOSURE

TK PC 1811-9-o



TK PC 1811-9-o

Empty enclosure

CUSTOMIZABLE

180 x 110 x 90 mm
Article number: 12040601

Empty enclosure - Industrial Quality -, base and cover: glass fibre reinforced polycarbonate

without knockouts

IP66 IK08 690V AC 1000V DC

Technical data

Measures

Width:	180 mm
Length:	110 mm
Height:	90 mm
Inner height:	75 mm

Material

Base:	Polycarbonate, glass-fibre reinforced, grey similar to RAL 7035
Cover:	Polycarbonate, glass-fibre reinforced, grey similar to RAL 7035
Sealing:	Polyurethane
Cover screw:	Polyamide 6, fiber-glass reinforced

Accessory

ASS-gro - External hinge set
HBA - Mounting material
MPS-KRI - Mounting plate
NS 35-144 - Mounting rail
NS 35-81 - Mounting rail
TK ABL - External fixing lugs kit
TK MPI-1811 - Mounting plate

Environmental attributes

Ambient temperature (min.):	-35 °C
Ambient temperature (max.):	80 °C
Ambient temperature (24 h):	60 °C
Max. rel. humidity at 25° C (short Therm):	95%
Max. rel. humidity at 40° C:	50%

Created on 2015-04-30. No responsibility is taken for the correctness of this information. Improvements for technical progress reserved.

Günther Spelsberg GmbH + Co. KG · Im Gewerbepark 1 · D-58579 Schalksmühle · Germany · Phone: +49 (0) 23 55 / 892-0 · Fax: +49 (0) 23 55 / 892-299

EMPTY ENCLOSURE

TK PC 1811-9-o

Other attributes

Ingress protection:	IP66 - acc. EN 60529 / DIN VDE 0470-1
Impact resistance:	IK08 acc. DIN EN 5012 / VDE 0470 segment 100
Protection class:	II - isolate protection acc. VDE 0106
Rated insulation voltage AC:	690 V V
Rated insulation voltage DC:	1000 V
Heavy metals-free:	Yes
PVC-free:	Yes
Silicone-free:	Yes
Fitted for outdoor application:	Yes
Combustion behaviour to UL 50 / UL 746C:	5VA nach UL 50 / UL 746C
Combustion behaviour to UL 94:	V-2 acc. UL 94
Combustion behaviour to VDE:	960°C acc. VDE 0471/ EN 60695
sealable:	Yes
Weatherproof:	Yes
Knockouts:	Yes

Günther Spelsberg GmbH + Co. KG · Im Gewerbepark 1 · D-58579 Schalksmühle · Germany · Phone: +49 (0) 23 55 / 892-0 · Fax: +49 (0) 23 55 / 892-299