Technical Data Sheet

Mode Number: 9102 4PRCCS

File Number: 2015-02-14-01

1. Name of cable:	**Telephone Cable**
2. P/N:	
3. Designed of cable:	
3.1 Inner conductor:	**Single copper steel Ø0.48±0.01mm**
3.2 Insulation:	**PVC**
3.3 Size of Insulation:	**Ø0.91±0.05mm**
3.4 Core colour:	**WH/BU WH/OG WH/GN WH/BN**
3.5 Two wires twisted to one pair:	
3.6 Four pairs twisted to a qual :	
3.7 Rip wire:	
4. Jacket:	**PVC**
4.1 Colour:	
4.2 Size:	**Ø5.1±0.5mm**
4.3 Wall thickness:	**≈0.5mm**
4.4 Printing:	**By request bargain**
5. Electric data at 20℃:	
5.1 Conductor resistance:	**≤650 Ohm/KM**
5.2 Insulation resistance:	**≥200M ohm*KM**
5.3 Testing voltage:	**wire/wire/screen 50Hz1min=800V**
6. Other requirement:	
6.1 Permissible temperature:	**-10℃----60℃**
6.4 Packing:	**100M on a non-returnable reel**
6.5 Test standard:	**This Technical Data Sheet**