GRIDPRO

CLICK Scolmore GROUP

Technical Specification

Product Code: GM2515BK **Description:** 2.4A Type A USB Charging Module





General Information

Dimensions (mm)	24.5 (W) x 50 (H) x 40 (D)		
Finish	Black		
Materials	Front Covers: Nylon	Rear Housing: Nylon	
	Electronics: USB Connections & Cable	Fixing Screws: Nickel Plated Steel	
Anti Microbial Certified	No		
Rated Voltage (V~) (Ue)	240	Frequency (Hz)	50/60
Resistive Load Rating (A)	2.4		
Termination Type	Screw		
Terminal Size (mm)	5 x 5	Terminal Torque Value (Nm)	1.2
Terminal Capacity - Solid (mm^2)	3 x 2.5, 2 x 4 or 1 x 6.0		
Product Marking	Charging USB Icon + 5V DC 2.4A		
Minimum Back Box Depth (mm)	35 (47 Flat Plate)		
Ingress Protection	IP20		
Operational Temperature (°C)	-5 to +40		
Warranty (Years)	2		

Standards
BS EN 62368-1
BS EN 61000-6-1
BS EN 61000-6-3

Additional Information
For cleaning / polishing of products, use only a soft, dry, clean cloth.
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.
Internally fused which enables direct mains supply.

CLIP-ON MODULES SCREW-IN MODULES

UK Patent: GB 2578427

Scolmore House, Mariner, Lichfield Road Industrial Estate,
Tamworth, Staffordshire, B79 7UL United Kingdom
T: +44 (0)1827 63454 | **F:** +44 (0)1827 63362
E: sales@scolmore.com | **W:** scolmore.com

CE UKCA

DoC Installation