SPECIFICATION SHEET

Product Code	CCA017

Description	20A Flex Outlet Plate





General Information	
Dimensions	86mm x 86mm x 9.5mm
Material composition	Front Plate: Urea Terminals: Brass Terminal Screws: Steel and Yellow Passivated Internal Busbars: Formed Press Brass Silver "On-lay" Copper/Brass Contacts
Back Box Depth	16mm – 47mm
Cable Size	4 x 2.5mm^2 or 1 x 6mm^2
Terminal Size	Live: 5mm Neutral: 5mm Earth: 5mm
Rating	20A
Flex Outlet	Yes (Through front & bottom of plate) 10mm
Warranty	10 Years Domestic

Standards	BS 5733

Additional Information	Ensure that the mains supply is isolated before commencing installation. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal. All white moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases. All products independently tested achieved a 99.9% kill rate across all four types of the strains of bacteria – MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae. Flex Outlet Diameter: 10mm

Errors & Omissions excluded. Specification is subject to change without notice.

V1.0

Scolmore International Limited
1 Scolmore Park, Landsberg, Lichfield Road Industrial Estate, Tamworth, Staffordshire, B79 7XB.

e sales@scolmore.com w www.scolmore.com
t 01827 63454 f 01827 63362