Data Sheet | Item Number: 887-952

Splicing Connector Set; L-BOXX® Mini; 221 Series

https://www.wago.com/887-952





This item includes:

Item No.: 221-412	Item No.: 221-413	Item No.: 221-415	Item No.: 221-500
COMPACT Splicing Connector; for all conductor types; max. 4 mm²; 2-conductor; with levers; transparent housing; Surrounding air temperature: max 85°C (T85); 4,00 mm²; transparent	COMPACT Splicing Connector; for all conductor types; max. 4 mm²; 3-conductor; with levers; transparent housing; Surrounding air temperature: max 85°C (T85); 4,00 mm²; transparent	COMPACT Splicing Connector; for all conductor types; max. 4 mm²; 5-conductor; with levers; transparent housing; Surrounding air temperature: max 85°C (T85); 4,00 mm²; transparent	Mounting carrier; 221 Series - 4 mm²; for DIN-35 rail mounting/screw mounting; orange
			4

Physical data

Width	260 mm / 10.236 inches
Height	63 mm / 2.48 inches
Depth	155 mm / 6.102 inches

Material data

Note (material data)	Information on material specifications can be found here
Fire load	14.701 MJ
Weight	836.1 g

Commercial data

eCl@ss 10.0	27-14-11-04
eCl@ss 9.0	27-14-11-04
ETIM 8.0	EC000446
ETIM 7.0	EC000446
PU (SPU)	1 pcs
Packaging type	Box
Country of origin	DE
GTIN	4055143616997
Customs tariff number	85369010000

Environmental Product Compliance

RoHS Compliance Status	Compliant,No Exemption

Downloads

Environmental Product Compliance

Compliance Search			
Environmental Product Compliance 887-952			

Documentation

Bid Text			
887-952	19.02.2019	xml 2.76 KB	
887-952	23.01.2019	docx 14.93 KB	