ECM06 Range

6 Watt Multi Head Range





Features :

- Interchangeable AC Heads
- DOE Level VI Efficiency
- Overcurrent Protection
- Short Circuit Protection
- RoHs Compliant
- 1 Year Warranty
- EN62368 Approved

Model		ECM-06-05	ECM-06-09	ECM-06-12	ECM-06-24
Output	DC Voltage	5vdc	9vdc	12vdc	24vdc
	Rated Current	1amp	0.6amp	0.5amp	0.25amp
	Current Range	0-1amp	0-0.6amp	0-0.5amp	0-0.25amp
	Rated Power	6 Watt	6 Watt	6 Watt	6 Watt
	Ripple & Noise	200mVp-p max	200mVp-p max	200mVp-p max	200mVp-p max
	Output Regulation	±5%	±5%	±5%	±5%
	Output Connector	2.1x5.5x12mm C+ve	2.1x5.5x12mm C+ve	2.1x5.5x12mm C+ve	2.1x5.5x12mm C+ve
Input	Voltage Range	90-264vac	90-264vac	90-264vac	90-264vac
	Frequency Range	47-63Hz	47-63Hz	47-63Hz	47-63Hz
	Input Current	1.2amp Max	1.2amp Max	1.2amp Max	1.2amp Max
	Inrush Current	40amp Max	40amp Max	40amp Max	40amp Max
	Standy Power	0.1W Max	0.1W Max	0.1W Max	0.1W Max
	Leakage Current	0.25amp Max	0.25amp Max	0.25amp Max	0.25amp Max
	Input Connector	UK, EU, US & AUS AC Heads	UK, EU, US & AUS AC Heads	UK, EU, US & AUS AC Heads	UK, EU, US & AUS AC Heads
Environment	Operating Temp	0°C~40°C	0°C~40°C	0°C~40°C	0°C~40°C
	Cooling	Convection	Convection	Convection	Convection
	Temperature Coefficient	0.05%/°C	0.05%/°C	0.05%/°C	0.05%/°C
	Humidity	5~95%RH(non-condensing)	5~95%RH(non-condensing)	5~95%RH(non-condensing)	5~95%RH(non-condensing)
	Storage Temp	-20°C~+80%°C	-20°C~+80%°C	-20°C~+80%°C	-20°C~+80%°C
Safety & EMC	Safety Standards	UL/CUL 62368-1, GS/TUV EN62368-1, SAA AS/NZ61558.2			
	EMC Emissions	EN55032,EN55035, FCC Part 15 Class B			

Mechanical Specification





Ecopac UK Power Ltd
Unit 4 Ridgeway
Crendon Industrial Area
Long Crendon
Buckinghamshire, HP18 9BF

www.ecopacpower.co.uk
Tel: +44 (0) 1844 204420
email :enquiry@ecopacpower.co.uk