Garant CEE 1 IP 44 cable reel for site & professional 20 m H07RN-F 5G2,5

For construction site use in accordance with DGUV 203-006 (formerly BGI 608) and permanent outdoor use IP 44.









MADE IN GERMANY

cable Pilot

3 YEARS MANUFACTURER GUARANTEE

DGUV-I 203-006 K2

VDE 0100 Teil 704

EN 61316

SPECIAL ROBUST

IP 44

Product number	1237990
EAN	4007123189335

DESCRIPTION

- In accordance with EN 61316.
- Reel body made of special plastic on galvanised support frame.
- Innovative „cablepilot“ carrying handle for perfect cable routing. Swings on both sides and enables convenient carrying and hanging.
- With twist handle for convenient retraction.
- RN cable is approved for harsh building conditions in accordance with VDE 0100 Part 704.
- CEE plug 400 V/16 A,
  – 1 CEE socket 400 V/16 A,
  – 2 splash-proof 230 V protective contact sockets.
- Sockets with earthing contact distributed on separate phases.
- With 3-pole safety cut-out and overheating protection.
- Category 2 equipment (K2 DGUV 203-005): Used for harsh operating conditions with high mechanical, physical and chemical impacts.

TECHNICAL DATA

Cable quality	Rubber-Neoprene
Cable length	20 m
Cable designation	H07RN-F 5G2,5
Cable colour	black
Reel diameter	320 mm
Plug system CEE socket	CEE 1x 16 A 3P+N+E (5p) 400 V
Plug system socket	Type F (Protective contact)
Plug system plug	CEE 16 A 3P+N+E (5p) 400 V
Max. current carrying capacity	16 A
Nominal input voltage	230 V/400 V
Degree of protection (IP)	IP44

PACKAGING, DIMENSIONS AND WEIGHTS

UP	1
Weight of product (without packaging)	8.22 kg
Dimension LxWxH (without packing)	32 cm x 25 cm x 41 cm
Weight of product (including packaging)	8.22 kg
Dimension LxWxH (incl. packing)	32 cm x 25.5 cm x 42 cm