GRIDPRO

Technical Specification

CLICK Scolmore GROUP

Product Code: GM2600BK **Description:** 300W Time Delay Switch Module





General Information

Dimensions (mm)	24.5 (W) x 50 (H) x 25 (D)		
Finish	Black		
Materials	Front Cover & Base: Nylon Terminals: Brass	Electronics: PCB & Electronic Components Terminal Screws: Steel & Yellow Passivated	
Anti Microbial Certified	No		
Rated Voltage (V~) (Ue)	230	Frequency (Hz)	50
Load Rating (W)	300		
Termination Type	Screw		
Terminal Capacity - Solid (mm^2)	2 x 1.5		
Minimum Back Box Depth (mm)	25 (35 Flat Plate)		
Ingress Protection	IP20		
Operational Temperature (°C)	-5 to +40		
Warranty (Years)	10	Warranty - Electronics (Years)	1

Standards

BS 5733

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Option to select 10 minute or 30 minute timer

CLIP-ON MODULES SCREW-IN MODULES

UK Patent: GB 2578427

Scolmore House, Mariner, Lichfield Road Industrial Estate,
Tamworth, Staffordshire, B79 7UL United Kingdom
T: +44 (0)1827 63454 | **F:** +44 (0)1827 63362
E: sales@scolmore.com | **W:** scolmore.com

UK CA

DoC Installation