ULM-164/SW - Line Mixer







Universal line mixer, 6 channels.

- 6 stereo inputs/mono inputs
- 2 stereo outputs, independent of each other (master 1 via RCA and 6.3 mm jack), 1 mono output
- 3-way equalizer
- LED VU meter, switchable for both outputs
- Clip LED for each channel
- Balance controls with centre click for the stereo input channels
- Extended muting function
- Adjustable headphone output
- 482 mm (19") rack installation, 1 RS

Technical Data

Line input, stereo	:	150 mV/50 k Ohm
Line input, mono	:	150 mV/25 k Ohm
Master output, stereo	:	1 V/600 Ohm
Master output, mono	:	2 V/600 Ohm
Headphones, stereo	:	≥ 8 Ohm
Frequency range	:	20-20,000 Hz
THD	:	0.05 %
S/N ratio	:	69 dB, unweighted
Equalizer, bass	:	±12 dB/80 Hz
Equalizer, midrange	:	±12 dB/1 kHz
Equalizer, treble	:	±12 dB/10 kHz
Power supply	:	230 V~/50 Hz/10 VA
Admiss. ambient temp.	:	0-40 °C
Dimensions	:	482x48x175 mm, 1 RS
Weight	:	2.3 kg
Line input, stereo	:	6 x RCA L/R
Line input, mono	:	6 x 6.3 mm jack, unbal.
Master output, stereo	:	2 x RCA (1 x 6.3 mm) L/R
Master output, mono	:	1 x 6.3 mm jack
Headphones	:	1 x 6.3 mm jack