Concordia Technologies
CABLING ACCESSORIES

Screw Mount Cable Ties



Product Details:

Material Natural: Polyamide 6.6 natural
Material Black: Polyamide 6.6 natural+ carbon black
Flammability of raw material: UL 94 - V2
4Humidity absorption: 2.4% (23° C - 50% R.H.)
Installation temperature: -10° C ÷ +85° C
Working temperature: -40° C ÷ +85° C
Max sustainable temperature for short time: +110°C
Carbon black addiction gives a better UV resistance
Halogen Free

Standards:

RoHS, Reach, PAHs Compliance

Application:

Good resistance to bases, oils, greases, oil derivates, chloride solvents. Limited resistance to acids. Not resistant to phenols.

Part No.	Size	Max.Bundle	Min.Bundle	Tensile Strength	Fasterner	Pack Size
ASMCT110X2.5N	110X2.5	19.0mm	3.0mm	80N	M2.5(4#)	100
ASMCT110X2.5B	110X2.5	19.0mm	3.0mm	80N	M2.5(4#)	100
ASMCT150X3.6N	150X3.6	35.5mm	3.5mm	180N	M4(8#)	100
ASMCT150X3.6B	150X3.6	35.5mm	3.5mm	180N	M4(8#)	100
ASMCT200X4.8N	200X4.8	49.8mm	3.5mm	230N	M5(10#)	100
ASMCT200X4.8B	200X4.8	49.8mm	3.5mm	230N	M5(10#)	100
ASMCT300X4.8N	300X4.8	82.8mm	3.5mm	230N	M5(10#)	100
ASMCT300X4.8B	300X4.8	82.8mm	3.5mm	230N	M5(10#)	100
ASMCT400X7.6N	400X7.6	109.2mm	8.5mm	540N	M6(1/4#)	100
ASMCT400X7.6B	400X7.6	109.2mm	8.5mm	540N	M6(1/4#)	100

This data sheet remains the property and copyright of C & C Cables Limited and the information contained within this document must not be copied or reproduced without the permission, in writing, from C & C Cables Limited. All information contained within this data sheet was correct at time of creation but may be subject to change without prior notice.

C & C Cables Limited Unit 1 & 2 Cotton Hall Mill, Cotton Hall Street, Darwen, BB3 0DW, UK