LED Work Light DINORA 5050 IP 65 5 m H07RN-F 2x1.0 5100 lm

For indoor and outdoor use, IP 65.











Product number	1171580001
EAN	4007123676538

DESCRIPTION

- Pleasant, glare-free work light and special light diffusion for large-area illumination.
- Perfect for commercial use and the demanding do-it-yourselfer.
- Lightweight yet very robust.
- Low heat generation, no risk of injury.
- Extremely long service life of the SMD LEDs, shock-resistant, maintenance-free.
- Break and impact resistant plastic housing with rubber edge protection.
- With fold-out, adjustable mounting bracket for setting up or attaching to brennenstuhl® tripods.
- Easy to transport, with carrying handle.
- With illuminated on/off switch.

TECHNICAL DATA

Cable quality	Rubber-Neoprene
Luminous flux	5100 lm
Power consumption	44.5 W
Luminous efficacy	115 lm/W
Energy efficiency class	A–G: E
Colour temperature	5700 K
Colour rendering index	80-89 (class 1B)
Min.-Max. Nominal input voltage	100 V - 240 V
Lifetime	54000 h
Cable length	5 m
Cable designation	H07RN-F 2X1,0
Impact strength	IK08
Protection class	II
Degree of protection (IP)	IP65
Colour	black/grey

PACKAGING, DIMENSIONS AND WEIGHTS

UP	1
Weight of product (without packaging)	2 kg
Dimension LxWxH (without packing)	9 cm x 28 cm x 25 cm
Weight of product (including packaging)	2.43 kg
Dimension LxWxH (incl. packing)	9.5 cm x 30 cm x 27.5 cm

SCOPE OF DELIVERY

LED work light DINORA 5050, 1x screw M6 50mm (for tripod)