OEM

Technical Datasheet

Product Code: PC241

Description: UK 13A Fused Fully Moulded Plug to Free End 3G 1.50mm² H05VV-F Cable Black - 2 Metre





General Information

Complete Powerlead Rating	13A/250V	
	Fully Moulded UK Plug	**Free End**
Component Rating	13A 250V~	N/A
Colour	Black	Black
Materials	Over Moulding Cover: PVC Pins and Connecting Plate: Brass Fuse Clip: Bronze Belt	
Cable Colour	Black	
Number of Conductors	3	
Conductor Cross Sectional Area	1.50mm²	
Number of Strands	48	
Conductor Material	Bare Copper (99.97%)	
Jacket Material	PVC	
Jacket Wall Thickness	0.9mm	
Jacket Elongation	150%	
Insulation Material	PVC (Colour Coded)	
Insulation Wall Thickness (mm)	0.7mm	
Insulation Elongation	150%	
Nominal Resistance	13.3 Ohm/Km	
Overall Cable Diameter	8.3mm	
Bend Radius	41.5°	
Rated Temperature	-15 to +70°C	
Cable Hanking	None	
Features	Class I protection	

Standards

BS 1363-1: 2016 +A1: 2018 (Kitemark Licence KM10807)
BS1362: 1973 plus Amendments 1 & 2 (ASTA File 1101)
DIN EN 50525-2-11: 2012-01 (VDE File 40010839)
BS EN 50525-2-11: 2011 (VDE File 40010839)

Scolmore House, Mariner, Lichfield Road Industrial Estate,
Tamworth, Staffordshire, B79 7UL United Kingdom
T: +44 (0)1827 63454 | **F:** +44 (0)1827 63362
E: sales@scolmore.com | **W:** scolmore.com

Errors & Omissions excluded.
Specification is subject to change without notice.