OEM

Technical Datasheet

Product Code: PC213

Description: UK 5A Non-rewireable Plug to Free End 3G 0.75mm² H05VV-F Cable Black - 2 Metre





General Information

Complete Powerlead Rating	5A/250V	
	Non-Rewireable UK Plug	**Free End**
	5A 250V~	N/A
Colour	Black	N/A
Materials	Body & Cover: PA Nylon Pins and Connecting Plate: Brass Fuse Clip: Bronze Belt	
Cable Colour	Black	
Number of Conductors	3	
Conductor Cross Sectional Area	0.75mm²	
Number of Strands	43	
Conductor Material	Bare Copper (99.97%)	
Jacket Material	PVC	
Jacket Wall Thickness	0.8mm	
Jacket Elongation	150%	
Insulation Material	PVC (Colour Coded)	
Insulation Wall Thickness (mm)	0.6mm	
Insulation Elongation	150%	
Nominal Resistance	26 Ohm/Km	
Overall Cable Diameter	6.5mm	
Bend Radius	32.5°	
Rated Temperature	-15 to +70°C	
Cable Hanking	200mm Fig. 8	

Standards

BS 1363-1: 2016 +A1: 2018
BS1362: 1973 plus Amendments 1 & 2
DIN EN 50525-2-11: 2012-01
EN 50525-2-11: 2011

Scolmore Park, Landsberg, Lichfield Road Industrial Estate,
Tamworth, Staffordshire, B79 7XB United Kingdom
T: +44 (0)1827 63454 | **F:** +44 (0)1827 63362
E: sales@scolmore.com | **W:** scolmore.com

Errors & Omissions excluded.
Specification is subject to change without notice.