# Garant S IP 44 cable reel 40 m AT-N05V3V3-F 3G1.5

For short-term outdoor use, IP 44.











MADE IN GERMANY

cable PILOT

3 YEARS MANUFACTURER GUARANTEE

IP 44

| | |
|---|---|
| **Product number** | 1198750 |
| **EAN** | 4007123683093 |

## DESCRIPTION

- Reel body made from rust-resistant and galvanised sheet steel fitted to a particularly sturdy galvanised steel tube frame.
- Innovative and ergonomic cable guide handle „cable pilot“ for perfect cable-management during winding. Handle commutes on both sides and allows easy carrying and cable storage. For right and left handed easy to rewind.
- Rotary handle for comfortable rolling up.
- The BREMAXX®-cable is extremely sturdy, applicable down to -35 °C, oil- and UV-resistant and highly abrasion-resistant.
- 3 water-jet protected earthed socket outlets with self-closing protective caps.
- Thermal cut-out protection, indicator shows overheating or overloading.

## TECHNICAL DATA

| | |
|---|---|
| **Cable quality** | BREMAXX |
| **Cable length** | 40 m |
| **Cable designation** | AT-N05V3V3-F 3G1,5 |
| **Cable colour** | orange |
| **Reel diameter** | 290 mm |
| **Plug system CEE socket** | Without |
| **Plug system socket** | Type F (Protective contact) |
| **Plug system plug** | Type E and F (Protective contact with earth hole) |
| **Max. current carrying capacity** | 16 A |
| **Nominal input voltage** | 230 V |
| **Degree of protection (IP)** | IP44 |

## PACKAGING, DIMENSIONS AND WEIGHTS

| | |
|---|---|
| **UP** | 1 |
| **Weight of product (without packaging)** | 5.88 kg |
| **Dimension LxWxH (without packing)** | 19.8 cm x 29 cm x 36.5 cm |
| **Weight of product (including packaging)** | 5.89 kg |
| **Dimension LxWxH (incl. packing)** | 19.8 cm x 29 cm x 36.5 cm |

## SCOPE OF DELIVERY

Garant S IP44 cable reel