Drill Driver CXT®

DF333DWAE

12V max • 30 Nm • 0 – 1 700 min^{-1}

Light tool for drilling and screwdriving

A compact tool for drilling and screwdrivers for fitters and maintenance staff and for home use. Thanks to its small size, this tool is easy to use and offers access to tight places. A max. torque of 30 / 14 Nm and two speed ranges. Two 2.0Ah batteries and a rapid charger in a carrying case.



CXT

Technical specifications

CXT Battery	✓
Nominal Battery Voltage	12 V
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
No load speed	0 - 450 / 0 - 1700 min^{-1}
Max. fastening torque Hard/Soft	30 / 14 Nm
Torque setting	20
Max Torque	34 Nm
Max. Drilling Diameter in Wood	21 mm
Drilling Capacity Wood (Auger Bit)	21 mm
Drilling Capacity Wood (Self-feed bit)	42 mm
Max. Drilling Diameter in Steel	10 mm
Driving Shank	3/8 "
Drill Chuck Capacity	0,8 - 10 mm
Sound Pressure Level (L_{pA})	71 dB(A)

0 088381 872614

Standard accessories

251314-2 - Truss Head Screw M4*12, Td140D | **346909-5** - Belt Hook | **784244-7** - Screw Bit, Ph2 – Ph2, 50 Mm, Double End | **821661-1** - Plastic Carrying Case

Standard machines

BL1021B - Battery CXT® 2,0 Ah | **DC10WD** - Battery Charger CXT®