KÄUDEN™

Item Code – PDU6/SGE
6 Way 13 Amp Slimline Surge Protected Power Distribution Unit (PDU)



- 19” 1U Horizontal Rack Mounting Slimline PDU with Surge Protection
- Protecting sensitive electronic circuits . Max Surge 4500 Amps
- Metal oxide semi-conductors absorb any unwanted energy
- Surge protection light to indicate functionality + required earth terminal
- 3 Metres mains cable with on/off switch

Will fit all 19”Rack Cabinets. If the unit suffers a worst-case strike, then internal thermal fuses will blow, and the green light will go out to warn you that the Surge Protection longer functions . An Earth Terminal is provided and should be used to provided full safety due to the the three-way protection circuit used on Rack Mount PDUs.

General

Sale Unit	Plain Cardboard Box	
Barcode		
Commodity Code	85444219	
Dimension Packed	70x145x540	Height Width Depth
Dimension loose	45x482.6x45	Height Width Depth
Weight Packed	1.7kg	
Weight Loose	-	
RoHS3 Compliant	Yes	

For Trade and Bulk buyers

Carton Quantity	10	
Dimension	55x35x29.5cm	
Weight	12kg NETT	14kg Gross

Technical

Protected	L-N L-E N-E
Withstanding Surge Current	4500A Standard Surge 6500A High Surge
Max allowable Voltage	320V AC 415DC
Max clamping Voltage	845V
Max energy	120 J Standard Surge 180 J High Surge

Standards

BS1362/2

BS EN IEC 623681- 2020 AMD 11

