GRIDPRO

CLICK Scolmore GROUP

Technical Specification

Product Code: GM2008RTBK **Description:** 250V~ Illuminated Blank Module





General Information

Dimensions (mm)	24.5 (W) x 50 (H) x 19.5 (D)		
Finish	Black		
Insert Colour	Red LED		
Materials	Transparent Trim: Polycarbonate Rear Housing: Nylon Terminal Screws: Steel & Yellow Passivated	Blank Section: Polycarbonate Terminals: Brass	
Anti Microbial Certified	No		
Rated Voltage (V~) (Ue)	250	Frequency (Hz)	50
Termination Type	Screw		
Terminal Size (mm)	Ø5	Terminal Torque Value (Nm)	1.2
Terminal Capacity - Solid (mm^2)	3 x 2.5, 2 x 4		
LED Indicator	Yes	Indicator Colour	Red
Minimum Back Box Depth (mm)	25 (35 Flat Plate)		
Ingress Protection	IP20		
Operational Temperature (°C)	-5 to +40		
Warranty (Years)	10	Warranty - Electronics (Years)	1

Standards

BS 5733

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.
Bespoke laser etching is available on request.

CLIP-ON MODULES SCREW-IN MODULES

UK Patent: GB 2578427

Scolmore House, Mariner, Lichfield Road Industrial Estate,
Tamworth, Staffordshire, B79 7UL United Kingdom
T: +44 (0)1827 63454 | **F:** +44 (0)1827 63362
E: sales@scolmore.com | **W:** scolmore.com

UK CA

DoC Installation