MAX620H250S



-Waterproof and dustproof IP67 certified

-Mil Specs (STANAG 4280, DEF STAN 81-41)

-Watertight seal around lid

-Automatic pressure release valve

-Easy to open double throw latches

-Load tested soft grip handle

-Holes for double padlocking

-Stackable interlocking system

-Thick body material

-Fully length hinges

-Nylon pins, corrosion free

Body and handle: polypropylene copolymer
Latches: nylon
Pins: nylon + 30% fiberglass
O-ring: polymer

COLOURS: black
EXTERNAL DIMENSIONS: 687 x 528 x H276 mm (27.05 x 20.79 x H10.86 inch)
INTERNAL DIMENSIONS: 620 x 460 x H250 mm (24.40 x 18.11 x H9.84 inch)
LID-BOTTOM DEPTH: 60 + 190 mm (2.36 + 7.48 inch)
WEIGHT WITH FOAM: 8.14 kg – 17.94 LBS
CARTON DIMENSIONS: 720 x 540 x 320mm – 28.34 x 21.26 x 12.60 inch
PCS PER CARTON: 1
WEIGHT OF THE FULL CARTON WITH FOAMS: 9.54 kg – 21.03 lbs.
MOULDING: injection molded
RANGE TEMPERATURE: -30 / 90°C (-22 / 194°F)
FEATURES: wheels, IP67, STANAG 4280, DEF STAN 81-41
CUSTOMIZATION: personalized nameplate/resin label
ACCESSORIES: cubed foams