TECHNICAL DATA SHEET

RoHS Compliant

FIBREGLASS BRAIDED TUBING

MODELS: PP01922-PP01937



Characteristics:

Operating temperature: -40°C to +200°C
Temperature tolerance: 265°C ±2°C x 168 hours ≥½ original voltage value
Thermal ageing test: 250°C x 24 hours, no crack
Cold bend: No crack
Vertical flame test: VW-1
Breakdown voltage: 1.2-7kV
Volume resistivity: ≥1,011Ω/cm
Colour: White
Length: 5m, 50m, 100m

Application:

Fibreglass sleeving coated silicone resin with a high temperature treatment. Outstanding temperature classification of 200°C. Excellent flame resistance, wear resistance, tear resistance, flexible, and insulation properties. Widely used in areas such as the internal wiring of electronics, electrical appliances, automotive, motors, household appliances etc.

Important Notice: This data sheet and its contents (the "Information") belong to pro-POWER. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but pro-POWER assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where pro-POWER was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict pro-POWER's liability for death or personal injury resulting from its negligence.

TECHNICAL DATA SHEET

RoHS Compliant

Product Dimensions:

Dimensions (mm)		
Inner Diameter	**Allowance**	**Min. WT**
3	+0.3, -0.1	≥0.25
3.5		
4		
4.5		
5	+0.4, -0.1	≥0.3
5.5		
6		
7		
9	+0.4, -0.2	
10	+0.5, -0.2	≥0.4
12	+1, -1	
13		
14		
15		
16		

Models:

Silicone Coated Fibreglass Braided Sleeving, 3mm, White, 100m	PP01922
Silicone Coated Fibreglass Braided Sleeving, 3.5mm, White, 100m	PP01923
Silicone Coated Fibreglass Braided Sleeving, 4mm, White, 100m	PP01924
Silicone Coated Fibreglass Braided Sleeving, 4.5mm, White, 100m	PP01925
Silicone Coated Fibreglass Braided Sleeving, 5mm, White, 100m	PP01926
Silicone Coated Fibreglass Braided Sleeving, 5.5mm, White, 100m	PP01927
Silicone Coated Fibreglass Braided Sleeving, 6mm, White, 100m	PP01928
Silicone Coated Fibreglass Braided Sleeving, 7mm, White, 100m	PP01929
Silicone Coated Fibreglass Braided Sleeving, 9mm, White, 50m	PP01930
Silicone Coated Fibreglass Braided Sleeving, 10mm, White, 50m	PP01931
Silicone Coated Fibreglass Braided Sleeving, 12mm, White, 50m	PP01932

Important Notice: This data sheet and its contents (the "Information") belong to pro-POWER. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but pro-POWER assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where pro-POWER was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict pro-POWER's liability for death or personal injury resulting from its negligence.

TECHNICAL DATA SHEET

RoHS Compliant

Silicone Coated Fibreglass Braided Sleeving, 13mm, White, 50m	PP01933
Silicone Coated Fibreglass Braided Sleeving, 14mm, White, 50m	PP01934
Silicone Coated Fibreglass Braided Sleeving, 15mm, White, 50m	PP01935
Silicone Coated Fibreglass Braided Sleeving, 16mm, White, 50m	PP01936
Silicone Coated Fibreglass Braided Sleeving, 4mm, White, 5m	PP01937

Important Notice: This data sheet and its contents (the "Information") belong to pro-POWER. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but pro-POWER assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where pro-POWER was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict pro-POWER's liability for death or personal injury resulting from its negligence.