GRIDPRO

# Technical Specification

**Product Code:** GM2047-LBK **Description:** 13A Fused Connection Lockable Module





## General Information

| | | | |
|---|---|---|---|
| Dimensions (mm) | 24.5 (W) x 50 (H) x 25 (D) | | |
| Finish | Black | | |
| Insert Colour | Black | | |
| Materials | Body & Insert: Nylon<br>Terminals: Brass | Internal Busbars: Brass<br>Terminal Screws: Steel & Yellow Passivated | |
| Anti Microbial Certified | No | | |
| Rated Voltage (V~) (Ue) | 250 | Frequency (Hz) | 50 |
| Resistive Load Rating (A) | 13 | | |
| Fuse Fitted Rating & Type | 13A (BS 1362) | | |
| Termination Type | Screw | | |
| Terminal Size (mm) | Ø5 | Terminal Torque Value (Nm) | 1.2 |
| Terminal Capacity - Solid ($mm^2$) | 3 x 2.5, 2 x 4 | | |
| Product Marking | Fused Symbol | | |
| Minimum Back Box Depth (mm) | 25 (35 Flat Plate) | | |
| Ingress Protection | IP20 | | |
| Operational Temperature (°C) | -5 to +40 | | |
| Warranty (Years) | 10 | | |

**Standards** BS 1363-4
BS 1362

**Additional Information**

For cleaning / polishing of products, use only a soft, dry, clean cloth.
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

UK Patent: GB 2578427

Scolmore House, Mariner, Lichfield Road Industrial Estate,
Tamworth, Staffordshire, B79 7UL United Kingdom
**T:** +44 (0)1827 63454 | **F:** +44 (0)1827 63362
**E**: sales@scolmore.com | **W:** scolmore.com

CLIP-ON MODULES SCREW-IN MODULES

DoC Installation