definity™ COMPLETE

Technical Specification

CLiCK® Scolmore GROUP

Product Code: SFBK164 **Description:** 4 Gang 2 Way 100W Dimmer Switch





General Information

Insert Dimensions (mm)	142.5 (W) x 82.5 (H) x 2.5 (D)		
Plate Dimensions (mm)	146 (W) x 86 (H) x 4 (D)		
Plate Fixing Centres - Horizontal (mm)	120.6		
Style	Screwless Complete		
Finish	Matt Black		
Compatible Cover Plate	SCP244#		
Materials	Cover Plate: Polycarbonate	Insert: Polycarbonate	
	Rear Housing: Nylon	Terminals: Brass	
	Terminal Screws: Steel & Yellow Passivated	PCB: Mixed Components	
	Earth Strap: Mild Steel		
Anti Microbial Certified	No		
Rated Voltage (V~) (Ue)	250	Frequency (Hz)	50
Load Rating (W)	5 - 100		
Load Rating Comments	Suitable For LED		
Termination Type	Screw		
Terminal Size (mm)	Ø3.5	Terminal Torque Value (Nm)	0.25
Terminal Capacity - Solid (mm²)	2 x 1.5		
2 Way Switch	Yes		
Switch Control Type	Press - ON/OFF, Rotate - Dim		
Dimmer Technology Type	Trailing Edge		
Minimum Brightness Programming	Available		
Minimum Back Box Depth (mm)	35		
Ingress Protection	IP20		
Operational Temperature (°C)	-5 to +40		
Warranty (Years)	10	Warranty - Electronics (Years)	1

Standards

BS EN 60669-1
BS EN 60669-2-1
BS EN 55015
BS EN 61000-3-2

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
We recommend the use of branded LED lamps with all Definity® Complete trailing edge dimmers. The use of inferior, non-branded lamps may require the nominal rating of the dimmer to be reduced. For further information please contact Click® Technical support team.
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Scolmore House, Mariner, Lichfield Road Industrial Estate,
Tamworth, Staffordshire, B79 7UL United Kingdom
T: +44 (0)1827 63454 | **F:** +44 (0)1827 63362
E: sales@scolmore.com | **W:** scolmore.com

CE UKCA

DoC Installation