GRIDPRO

CLICK Scolmore GROUP

# Technical Specification

**Product Code:** GM2305BK **Description:** VGA Module



## General Information

| | | | |
|---|---|---|---|
| Dimensions (mm) | 24.5 (W) x 50 (H) x 43 (D) | | |
| Finish | Black | | |
| Materials | Front Cover: Nylon<br>Fixing Screws: Nickel Plated Steel | Electronics: VGA Connections & Cable | |
| Anti Microbial Certified | No | | |
| Rated Voltage (DC) | 5 | | |
| Flylead Cable Length (mm) | 110 | | |
| Flylead Overall Length (mm) | 160 | | |
| Pre-wired Cable Specification | HD15 | | |
| Shielded | Yes | | |
| Minimum Back Box Depth (mm) | 47 | | |
| Ingress Protection | IP20 | | |
| Operational Temperature (°C) | -5 to +40 | | |
| Warranty (Years) | 10 | Warranty - Electronics (Years) | 1 |

## Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

CLIP-ON MODULES SCREW-IN MODULES

UK Patent: GB 2578427

Scolmore House, Mariner, Lichfield Road Industrial Estate,
Tamworth, Staffordshire, B79 7UL United Kingdom
**T:** +44 (0)1827 63454 | **F:** +44 (0)1827 63362
**E**: sales@scolmore.com | **W:** scolmore.com

DoC Installation